



مدل	مشخصات فنی	عکس محصول	قیمت
IP CAMERA DP-644-Q42  	کیفیت تصویر : ۴ مگاپیکسل – وارم لایت – تشخیص انسان 1.3 " 4MP 25fps LOW Lux CMOS SENSOR -Warm LED H.265+ video coding, Support body detection & mark human;frame, Enabled with ONVIF protocol and NETCOM. With 0.5TAlgorithm ,more accurate with human recognition-- 12v DC	 Plastic case	1,466,000T
IP CAMERA DP-644-Q42-P  	کیفیت تصویر : ۴ مگاپیکسل – وارم لایت – تشخیص انسان 1.3 " 4MP 25fps LOW Lux CMOS SENSOR -Warm LED H.265+ video coding, Support body detection & mark human;frame, Enabled with ONVIF protocol and NETCOM. With 0.5TAlgorithm ,more accurate with human recognition POE +12v DC	 Plastic case	-
IP CAMERA DP-644-HQ42  	کیفیت تصویر : ۴ مگاپیکسل – وارم لایت – تشخیص انسان 1.3 " 4MP 25fps LOW Lux CMOS SENSOR -Warm LED H.265+ video coding, Support body detection & mark human;frame, Enabled with ONVIF protocol and NETCOM. With 0.5TAlgorithm ,more accurate with human recognition +12v DC	 metal and plastic case	1,772,000T
IP CAMERA DP-644-HQ42-P  	کیفیت تصویر : ۴ مگاپیکسل – وارم لایت – تشخیص انسان 1.3 " 4MP 25fps LOW Lux CMOS SENSOR -Warm LED H.265+ video coding, Support body detection & mark human;frame, Enabled with ONVIF protocol and NETCOM. With 0.5TAlgorithm ,more accurate with human recognition POE +12v DC	 metal and plastic case	2,027,000 T
IP CAMERA DP-655-DX53  	کیفیت تصویر : ۵ مگاپیکسل – وارم لایت – تشخیص انسان 1/3" 5MP 20fps LOW CMOS SENSOR , Warm LED H.265+ video coding, Support body detection and mark human frame, Enabled with ONVIF protocol and NETCOM- 12v DC -2.8mm		2,398,000 T



IP CAMERA

کیفیت تصویر : ۵ مگاپیکسل – وارم لایت – تشخیص انسان

DP-655-DX53-P



1/3" **5MP 20fps** LOW CMOS SENSOR , Warm LED; H.265+ video coding, Support body detection and mark human frame, Enabled with ONVIF protocol and NETCOM-**POE +12v DC-2.8mm**



2,653,000 T

IP CAMERA

کیفیت تصویر : ۵ مگاپیکسل سونی – وارم لایت – تشخیص انسان

DP-655S-DX



1/2.8" **5MP 25fps** CMOS sensor ; Warm light; Support H.265+, H.265, H.264 encoding ; Support soft photosensitive: full color mode, ; Support intelligent analysis: precise human shape detection, area detection, and trip line detection ; Support Onvif ; Provide SDK (WINDOWS, Android, Linux) **4mp/30fps-SONY335 original- 12v DC-2.8mm**



3,958,000 T

IP CAMERA

کیفیت تصویر : ۵ مگاپیکسل سونی – وارم لایت – تشخیص انسان

DP-655S-DX-P



1/2.8" **5MP 25fps** CMOS sensor ; Warm light; Support H.265+, H.265, H.264 encoding ; Support soft photosensitive: full color mode, ; Support intelligent analysis: precise human shape detection, area detection, and trip line detection ; Support Onvif ; Provide SDK (WINDOWS, Android, Linux) **4mp/30fps-SONY335 original- POE+12v DC-2.8mm**



4,213,000 T

IP CAMERA

کیفیت تصویر : ۵ مگاپیکسل سونی – وارم لایت – تشخیص انسان

DP-655S-HQ-P



1/2.8" **5MP 25fps** CMOS sensor ; Warm light; Support H.265+, H.265, H.264 encoding ; Support soft photosensitive: full color mode, ; Support intelligent analysis: precise human shape detection, area detection, and trip line detection ; Support Onvif ; Provide SDK (WINDOWS, Android, Linux) **4mp/30fps-SONY335 original- POE+12v DC-2.8mm metal and plastic case**



4,123,000 T



کیفیت تصویر : ۲ مگاپیکسل سونی - وارم لایت - تشخیص انسان

IP CAMERA

BP-603BX-IM-P



1/2.8" **2MP** Sony IMX307 STARVIS
CMOS;Maximum resolution up to
1920×1080@30fps;True Day/Night, 3D DNR, Digital
WDR;Support humanoid detection, motion
detection;Support the Tuya P2P on Android,
IOS;Support two way audio, Built-in audio amplifier
function;Support ONVIF and XM protocol;Support
TCP/IP/HTTP/NTP/DHCP/SMTP/RTSP;Open
SDK(Linux,Windows), CGI,easily to be integrated
with other digital systems;Support OPENIPC
development-**lens 12mm +12V DC**



5,928,000T

IP CAMERA

BP-604-TX



کیفیت تصویر : ۴ مگاپیکسل - وارم لایت - تشخیص انسان

1.3 " **4MP 25fps** LOW Lux CMOS SENSOR -Warm
LED H.265+ video coding, Support body detection &
mark human;frame, Enabled with **ONVIF** protocol
and NETCOM. With 0.5TAlgorithm ,more accurate
with human recognition—**12v DC**



1,797,000T

IP CAMERA

BP-604-TX-P



کیفیت تصویر : ۴ مگاپیکسل - وارم لایت - تشخیص انسان

1.3 " **4MP 25fps** LOW Lux CMOS SENSOR -Warm
LED H.265+ video coding, Support body detection &
mark human;frame, Enabled with **ONVIF** protocol
and NETCOM. With 0.5TAlgorithm ,more accurate
with human recognition **POE +12v DC**



2,073,000T

IP CAMERA

BP-605-TS53



کیفیت تصویر : ۵ مگاپیکسل - وارم لایت - تشخیص انسان

1/3" **5MP 20fps** LOW CMOS SENSOR , Warm
LED; H.265+ video coding, Support body detection
and mark human frame, Enabled with ONVIF protocol
and NETCOM- **12v DC**



2,285,000T

IP CAMERA

BP-605-TS53-P



کیفیت تصویر : ۵ مگاپیکسل - وارم لایت - تشخیص انسان

1/3" **5MP 20fps** LOW CMOS SENSOR , Warm
LED; H.265+ video coding, Support body detection
and mark human frame, Enabled with ONVIF protocol
and NETCOM-**POE +12v DC**



2,545,000T

IP CAMERA

BP-605-BX53-P



کیفیت تصویر : ۵ مگاپیکسل - وارم لایت - تشخیص انسان

1/3" **5MP 20fps** LOW CMOS SENSOR , Warm
LED; H.265+ video coding, Support body detection
and mark human frame, Enabled with ONVIF protocol
and NETCOM-**POE +12v DC**



کیس بزرگ

2,988,000T



کیفیت تصویر : ۵ مگاپیکسل سونی - وارم لایت - تشخیص انسان

IP CAMERA

BP-605-TS12



1/2.8" **5MP 25fps** CMOS sensor ; **Warm light**;Support H.265+, H.265, H.264 encoding ; Support soft photosensitive: full color mode, ; Support intelligent analysis: precise human shape detection, area detection, and trip line detection ; Support Onvif ; Provide SDK (WINDOWS, Android, Linux) **4mp/30fps-SONY335 original- 12v DC**



3,993,000T

IP CAMERA

BP-605-TS12-P



کیفیت تصویر : ۵ مگاپیکسل سونی - وارم لایت - تشخیص انسان
1/2.8" **5MP 25fps ; Warm light**;Support H.265+, H.265, H.264 encoding: full color mode, ; Support intelligent analysis: precise human shape detection, area detection, and trip line detection ; Support Onvif - **4mp/30fps-SONY335 original- POE+12v DC- 3.6mm**



4,253,000T

IP CAMERA

BP-605-TS12-P8



کیفیت تصویر : ۵ مگاپیکسل سونی - وارم لایت - تشخیص انسان
1/2.8" **5MP 25fps ; Warm light**;Support H.265+, H.265, H.264 encoding: full color mode, ; Support intelligent analysis: precise human shape detection, area detection, and trip line detection ; Support Onvif - **4mp/30fps-SONY335 original- POE+12v DC- 8MM LENS ZOOM**



4,440,000T

IP CAMERA

BP-605-BX12-P



کیفیت تصویر : ۵ مگاپیکسل سونی - وارم لایت - تشخیص انسان
1/2.8" **5MP 25fps** CMOS sensor ; **Warm light**;Support H.265+, H.265, H.264 encoding ; Support soft photosensitive: full color mode, ; Support intelligent analysis: precise human shape detection, area detection, and trip line detection ; Support Onvif ; Provide SDK (WINDOWS, Android, Linux) **4mp/30fps-SONY335 original- POE+12v DC**



کیس بزرگ
4,904,000T

IP CAMERA

BP-608S-TS-P



کیفیت تصویر : ۸ مگاپیکسل سونی - وارم لایت - تشخیص انسان
1/2.8" **8MP** black light CMOS sensor;**warmlight**;With 1T computing power;Support Smart H.265+, H.265, H.264 encoding;Support 2 kinds of light signal control: CDS, PWM signal;Support soft photosensitive:



6,632,000 T



full color mode, infrared mode, dual light mode;Support image flip, support HDR;Support intelligent analysis: humanoid detection, SupportOnvifprotocol;Support character overlay, privacy maskIP address, extension;Provide SDK development kit (WINDOWS, Android, Linux;

SONY415 original- POE+12v DC

کیفیت تصویر : ۸ مگاپیکسل سونی - وارم لایت - تشخیص انسان

IP CAMERA

BP-608S-BX-BP



1/2.8" **8MP** black light CMOS sensor;**warmlight**;With 1T computing power;Support Smart H.265+, H.265, H.264 encoding;Support 2 kinds of light signal control: CDS, PWM signal;Support soft photosensitive: full color mode, infrared mode, dual light mode;Support image flip, support HDR;Support intelligent analysis: humanoid detection, SupportOnvifprotocol;Support character overlay, privacy maskIP address, extension;Provide SDK development kit (WINDOWS, Android, Linux;

SONY415 original- POE+12v DC



کیس بزرگ

6,830,000T

NVR RECORDER

NVR-9808-MS

8CH-5MP

preview Main stream 25fps ; Substream 25fps;play back 1*5M/25(Main stream) 8*D1/25(Substream) 1*5M/25(Main stream) 4*720P/25(Substream) ; Supports various mobile phone monitoring (iPhone Android);Support VGA, HDMI output at the same time .Powerful network services (supporting DHCP, FTP, DNS, DDNS, NTP, UPNP, Email, etc.), complete supporting facilities (WEB, client, SDK), easily achieve interconnection and interoperability.Supports more than 12 languages and breaks the limits of national borders.Freely change the startup interface and choose the interface style.The main mode supports main stream and sub-stream recording.The main mode supports full channel playback.Support Dana Cloud Taoshi Cloud cloud platform customization .H.264/H.265 ;1G RAM; 1080P; 1HARD TO 6TB;**wireless mouse**



3,994,000T

NVR RECORDER

NVR-9816-4K

16CH-5MP

8CH-8MP

preview Main stream 25fps ; Substream 25fps;play back 1*5M/25(Main stream) 16*D1/25(Substream) 1*8M/25(Main stream) 8*720P/25(Substream); Supports various mobile phone monitoring (iPhone Android).Support multiple web browsers (IE / Chrome / Firefox / Safari).Support VGA, HDMI output at the same time.Powerful network services (supporting DHCP, PPPOE, FTP, DNS, DDNS, NTP, UPNP, Email, etc.), complete supporting facilities (WEB, client, SDK), easily achieve interconnection and interoperability.Supports more than 20 languages and breaks the limits of national borders.Freely change the startup interface and choose the interface style.The main



4,495,000T



mode supports main stream and sub-stream recording.The main mode supports full channel playback.Support Dana Cloud Taoshi Cloud cloud platform customization; H.264/H.265;2G RAM ; 1HARD TO 6TB;**wirless mouse**

preview Main stream 25fps ; Substream 25fps; play back 1.9*5M/25(Main stream) 1*8M/25(Main stream) 16*D1/25 (Substream) 1*8M/25(Main stream) 8*D1/25 (Substream) ;Supports various mobile phone monitoring (iPhone Android).Support multiple web browsers (IE / Chrome / Firefox / Safari).Support VGA, TV, HDMI output at the same time.Powerful network services (supporting DHCP, PPPOE, FTP, DNS, DDNS, NTP, UPNP, Email, etc.), complete supporting facilities (WEB, client, SDK), easily achieve interconnection and interoperability.Supports more than 20 languages and breaks the limits of national borders.Freely change the startup interface and choose the interface style.Support Dana Cloud Taoshi Cloud cloud platform customization; H.264/H.265; 4G RAM ; 2 HARD TO 6TB**wirless mouse**

NVR RECORDER

NVR-9832-4K



8,545,000T

AHD CAMERA

DH-202-Q83



With **2MP** CMOS, Capture moving images;Support AHD/TVI/CVI , excellent performance clear picture;Support IR-CUT,CDS external control ,D/N;Support OSD/UTC;Support DWDR, low light automatic frame reduction and defogging;Adaptive Digital Noise Reduction, 3D-DNR, 2D-DNR;Support PWM light adjust/No photosensitive control;6KV Lighting protection, with ECAP 220u;Support DC 6-15V power;32x32/38x38mm



Plastic case

898,000T

AHD CAMERA

DH-202-DX53



With **2MP** CMOS; Capture moving images;Support AHD/TVI/CVI;excellent performance clear picture;0.01Lux@(F1.2,AGC ON);0LUX with IR;Support IR-CUT,CDS external control ,D/N;Support OSD/UTC;SupportDWDR;Adaptive Digital Noise Reduction, 3D-DNR, 2D-DNR;6KV Lighting protection, with ECAP 220u;Support DC 6-15V power;32x32/38x38 (mm); video outputAHD/TVI/CVI/CVB5;1080P@25FPS/1080P@30FPS;



-



AHD CAMERA

DH-205-HQ83-A



5MP HD CMOS Coaxial high-definition output, with excellent performance, clear and bright picture;Support MIC with TVI signal only.;Lux: 0.05Lux@(F1.2,AGC ON);0LUX with IR.;Support IR-CUT,CDS external control , D/N;Support OSD and Customization;Support Cable Switching the output signal function;Adaptive Digital Noise Reduction, 2D-DNR;Support UTC;Support 2 ways PWM output(Customized software);Support 1 way AD input.;Support wide power range 8-15V output.



1,413,000T

AHD CAMERA

DH-205-DX83-A



5MP HD CMOS Coaxial high-definition output, with excellent performance, clear and bright picture;Support MIC with TVI signal only.;Lux: 0.05Lux@(F1.2,AGC ON);0LUX with IR.;Support IR-CUT,CDS external control , D/N;Support OSD and Customization;Support Cable Switching the output signal function;Adaptive Digital Noise Reduction, 2D-DNR;Support UTC;Support 2 ways PWM output(Customized software);Support 1 way AD input.;Support wide power range 8-15V output.



1.540.000 T

AHD CAMERA

BH-202-CH83



With **2MP** CMOS; Capture moving images;Support AHD/TVI/CVI;excellent performance clear picture;0.01Lux@(F1.2,AGC ON);0LUX with IR;Support IR-CUT,CDS external control ,D/N;Support OSD/UTC;SupportDWDR;Adaptive Digital Noise Reduction, 3D-DNR, 2D-DNR;6KV Lighting protection, with ECAP 220u;Support DC 6-15V power; video output AHD/TVI/CVI/CVB5;1080P@25FPS/1080P@30FPS;



1,160,000 T

AHD CAMERA

BH-205-TX83-A



5MP HD CMOS Coaxial high-definition output, with excellent performance, clear and bright picture;Support MIC with TVI signal only.;Lux: 0.05Lux@(F1.2,AGC ON);0LUX with IR.;Support IR-CUT,CDS external control , D/N;Support OSD and Customization;Support Cable Switching the output signal function;Adaptive Digital Noise Reduction, 2D-DNR;Support UTC;Support 2 ways PWM output(Customized software);Support 1 way AD input.;Support wide power range 8-15V output.



1,648,000 T



XVR RECORDER

XVR-5604-I

Preview 4*5MN@20fps;TVI/AHD/CVI/CVBS/IPC five-in-one function, multi-mode input, support HD analog video encoding, support HD analog + HD network video input, support pure HD network video input.;Easily implement network penetration through cloud services and remote monitoring in one step.;Supports various mobile phone monitoring (iPhone/Android).;Support multiple web browsers (IE/Chrome/Firefox/Safari).;Support VGA,HDMI output at the same time.;Powerful network services (supporting DHCP, PPPOE, FTP, DNS, DDNS, NTP, UPNP, Email, etc.), complete supporting facilities (WEB, client, SDK), easily achieve interconnection and interoperability.;Supports more than 20 languages and breaks the limits of national borders.;Freely change the startup interface and choose the interface style.;Support face human detection functions.;Support STVI function.;Support coaxial audio.;Support TS Cloud cloud platform customization.



4,056,000 T

XVR RECORDER

XVR-9408-N5

Preview 8*5MN@12.5fps;TVI / AHD / DVR / NVR / CVI five-in-one function, multi-mode input, support HD analog video encoding, support HD analog + HD network video input, support pure HD network video input.;Easily implement network penetration through cloud services and remote monitoring in one step.;Supports various mobile phone monitoring (iPhone Android).;Support multiple web browsers (IE / Chrome / Firefox / Safari).;Support VGA, HDMI output at the same time.;Powerful network services (supporting DHCP, PPPOE, FTP, DNS, DDNS, NTP, UPNP, Email, etc.), complete supporting facilities (WEB, client, SDK), easily achieve interconnection and interoperability.;Supports more than 20 languages and breaks the limits of national borders.;Freely change the startup interface and choose the interface style.;Support humanoid function.;Support STVI function.;Support coaxial audio.;Support Dana Cloud Taoshi Cloud cloud platform customization.



5.650,000 T



XVR RECORDER

XVR-5608-I

Preview 8*5MN@12.5fps;TVI / AHD / DVR / NVR / CVI five-in-one function, multi-mode input, support HD analog video encoding, support HD analog + HD network video input, support pure HD network video input.;Easily implement network penetration through cloud services and remote monitoring in one step.;Supports various mobile phone monitoring (iPhone Android).;Support multiple web browsers (IE / Chrome / Firefox / Safari).;Support VGA, HDMI output at the same time.;Powerful network services (supporting DHCP, PPPOE, FTP, DNS, DDNS, NTP, UPNP, Email, etc.), complete supporting facilities (WEB, client, SDK), easily achieve interconnection and interoperability.;Supports more than 20 languages and breaks the limits of national borders.;Freely change the startup interface and choose the interface style.;Support humanoid function.;Support STVI function.;Support coaxial audio.;Support Dana Cloud Taoshi Cloud cloud platform customization.



4,968,000T

XVR RECORDER

XVR-9416-N5

Preview 16*5MN@12.5fps;TVI / AHD / DVR / NVR / CVI five-in-one function, multi-mode input, support HD analog video encoding, support HD analog + HD network video input, support pure HD network video input.;Easily implement network penetration through cloud services and remote monitoring in one step.;Supports various mobile phone monitoring (iPhone Android).;Support multiple web browsers (IE / Chrome / Firefox / Safari).;Support VGA,TV,HDMI output at the same time.;Powerful network services (supporting DHCP, PPPOE, FTP, DNS, DDNS, NTP, UPNP, Email, etc.), complete supporting facilities (WEB, client, SDK), easily achieve interconnection and interoperability.;Supports more than 20 languages and breaks the limits of national borders.;Freely change the startup interface and choose the interface style.;Support basic intelligence and tripwire perimeter functions.;Support humanoid functions.;Support STVI function.;Support coaxial audio.;Support snapshot function.;Support Dana Cloud Taoshi Cloud cloud platform customization.



9,098,000 T



تمامی محصولات دارای ۲۴ ماه گارانتی

معتبر می باشد .

جهت اطلاع از قیمت های کارتنی و شرایط

تسویه چکی با کارشناسان مجموعه تماس

بگیرید .

1404/01/15